

H1BB 250V DC 500A-800A

Semiconductor Fuses

半导体保护熔断器



Standard/ 标准: UL 248-13, IEC 60269-4, GB/T 13539.4

INTERRUPTING CAPACITY / 分断能力:


50,000 A at 250V DC

Dimensions/ 尺寸:

Unit 单位: mm


Type: H1BB 200-450A

Part No.: H1BB(amp rating)



Type: H1BB 500-800A

Part No.: H1BB(amp rating)



TECHNICAL PARAMETERS/ 技术参数:

PART NO. 目录编号	CURRENT RATING 额定电流	SAFETY APPROVALS 安全认证		
		cURus	TUV	UKCA
H1BB200	200A	●	●	●
H1BB250	250A	●	●	●
H1BB315	315A	●	●	●
H1BB350	350A	●	●	●
H1BB400	400A	●	●	●
H1BB450	450A	●	●	●
H1BB500	500A	●	●	●
H1BB550	550A	●	●	●
H1BB630	630A	●	●	●
H1BB700	700A	●	●	●
H1BB800	800A	●	●	●

● DENOTES FOR APPROVAL
○ DENOTES FOR PENDING

● 表示已取得安全认证
○ 表示正在申请安全认证

H1BB 平均 I-T 曲线图 (仅供参考)

AVERAGE I-T CHARACTERISTICS CURVE (FOR REFERENCE)

